VP BUILDINGS TEXTURECLAD PANEL COLORS

Long-Term Beauty • Unmatched Protection • Superior Quality - You Get All Three



VP TEXTURECLAD WALL PANEL PAINT FINISHES

The VP TextureClad finish is a special fiber-reinforced Polymer/aggregate coating that is factory applied and oven cured to provide an attractive and durable finish permanently bonded to a roll-formed panel.

TEST	TEST METHOD*	TEST RESULTS
QUV Weatherometer	ASTM G 154-00, 1000 Hours ASTM D4214-98	No visual color changes. Chalking #8.
Humidity Test	ASTM D2247-97, 1000 hours	No change in hardness or other observable properties after 48 hours recovery.

^{*}Laboratory testing was conducted in accordance with standard accepted procedures utilized in the painting industry per American Society for Testing Materials (ASTM).

The test methods used were:

ASTM G154-00,	Standard Practice for Operating Fluorescent Light Apparatus for UV Exposure of Nonmetallic Materials	
ASTM D4214-98,	Standard Test Methods for Evaluating Degree of Chalking of Exterior Paint Films	
ASTM D2247-97,	Standard Practice for Testing Water Resistance of Coatings in 100% Relative Humidity.	

Actual paint colors may vary. Colors in this guide are a close representation of the products offered, but may not be an exact match. VP Buildings reserves the right to change color offerings shown here without notice. Metal panel samples are available upon request.

Note: All panels formed from light gauge metal may exhibit waviness, also known as "Oil Canning," commonly occurring in, but not restricted to, flat portions of a panel. This inherent characteristic is not a defect of material and is not cause for rejection









