

# VP WALL SYSTEMS

STYLE	FEATURES
<b>IMPRESSACLAD</b>	<b>SMOOTH OR EMBOSSED INTERLOCKING METAL WALL PANEL SYSTEM</b>



- Easy installation with concealed fasteners
- Clip-less design
- Panels to 26' length
- 20 year warranty
- 6 standard colors (custom colors available)
- Works great as a Soffit panel also

ImpressaClad provides a smooth or embossed finish in a stackable, lightweight and easy-to-install metal wall panel system.



**BUILD SMART BUILD GREEN WITH VP**  
RECYCLED STEEL COOL PAINTS ENERGY SAVING INSULATION



# PRE-FINISHED PANELS ARE EASY TO ASSEMBLE AND CAN BE INSTALLED REGARDLESS OF CLIMATE OR WEATHER CONDITIONS

## IMPRESSACLAD


ImpressaClad will satisfy most local building ordinances that prohibit other metal wall panel applications. These panels are durable and provide protection from ultraviolet rays.

Each ImpressaClad panel is manufactured from 20-gauge galvanized steel. Panel width installed is 16". Both top and bottom of every panel has a 5/8" fold back. Formed ends allow the panel to nest end-to-end for stacking up a vertical wall, allowing for taller elevation applications. Installation of panels over a weatherproof membrane is recommended. Panel lengths range from 14" to 26'.


The panels are available in 6 unique colors. Kynar paint finishes are respected for their durability, resistance and color retention. The swatches shown are an approximation of actual paint colors. Variations may occur between sample materials and finished product. For actual paint color, ask for a painted metal chip.

ImpressaClad comes with a 20-year warranty for the panel and finish.


Linen White



Taupe



Sandstone



Ash



Khaki



Gray



### FEATURES

- 16" width coverage; lengths up to 26'
- Durable, attractive finishes
- Concealed fastener installation
- Lightweight
- 6 unique colors
- Low-maintenance
- 24 and 20 ga. trims

CHARACTERISTICS	TEST METHOD
Adhesion	ASTM D2794
Formability	ASTM D1737
Color Retention	ASTM G26
Structural	ASTM E1592
Racking Shear	ASTM E72-80
Water Soak	ASTM D870
Salt Spray	ASTM B-117
Weathering	ASTM G23
Missile Test	ASTM E1886
Cyclic Pressure	ASTM E1996
<i>Dade County, Florida Approved</i>	

Note: All panels formed from light gauge metal may exhibit waviness, also known as "Oil Canning," commonly occurring in, but not restricted to, flat portions of a panel. This inherent characteristic is not a defect of material and is not cause for rejection.

Note: ImpressaClad finishes meet Kynar 500 specifications. KYNAR® is a registered trademark of Atochem North America, Inc.



**The Ultimate Building Solution**  
 VP Buildings  
 3200 Players Club Circle  
 Memphis, TN 38125  
 1-800-238-3246 • vp.com  
 2096 Issued 1/08

